
INDUSTRIAL COMPONENT DATA

# FOC-LC:A-LC:A-GZ02/2 1400621 PHOENIX CONTACT FO patch cable

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-LC:A-LC:A-GZ02/2**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FOC-LC:A-LC:A-GZ02/2 |
| Catalog number | 1400621 |
| Category | Fibre optic patch cord |
| Minimum order | 1 Pcs |
| Document ID | EO-B898ED472F |
| Generated | 2026-11-19 |

## Product Overview

FO patch cable
Ready-made fibre optic cable, zipcord cable, multimode fibreglass 50/125 um, OM3, connector: LC/LC, degree of protection: IP20, for cable ducting or control cabinet arrangements, length: 2 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1400621
Packing unit 1 pc
Catalog page Page 419 (C-2-2017)
GTIN 4046356734769
Weight per Piece (excluding packing) 44.500 g
Custom tariff number 85447000
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 2
Type of cable Zip cord
Length of cable 2.00 m
Color blue

Degree of protection IP20
IP20
Ambient conditions
Ambient temperature (operation) -10 °C ... 60 °C
Ambient temperature (assembly) -5 °C ... 50 °C
Ambient temperature (storage/transport) -10 °C ... 60 °C
Material data
Flammability rating according to UL 94 V0
External sheath, color aqua
Ferrule material Zirconia ceramics
Electrical characteristics
Transmission speed OM3
Standards and Regulations
Halogen-free complying with IEC 60754-1/2
Flammability rating according to UL 94 V0
Line characteristics
Type of cable Zip cord
Cable type Fiberglass
Cable abbreviation I-V(ZN)H
Wire colors -
External sheath, color aqua
Cable, attenuation 2.5 dB/km (at 850 nm), 0.7 dB/km (at 1300 nm)
Cable weight 15.80 kg/km
Smallest bending radius, fixed installation 15 mm
Smallest bending radius, movable installation 30 mm
Tensile strength short-term/long-term 600 N
cable layer type Indoors
Halogen-free complying with IEC 60754-1/2
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@s...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-LC:A-LC:A-GZ02/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.