INDUSTRIAL COMPONENT DATA

CABLE-FCN40/4X14/ 3,0M/IM/MEL 2903505 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-FCN40/4X14/ 3,0M/IM/MEL



Manufacturer	PHOENIX CONTACT
MPN / Reference	CABLE-FCN40/4X14/ 3,0M/IM/MEL
Catalog number	2903505
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-B43544BEEA
Generated	2026-11-19

Product Overview

Cable
Ready-made round cable; Control: Mitsubishi Electric MELSEC L, MELSEC Q, Honeywell MasterLogic ML200; connection 1: Fujitsu plug-in connector (1x 40-pole); connection 2: IDC/FLK connection female (4x 14-poles); Cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2903505
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 489 (C-5-2017)
GTIN 4046356745437
Weight per Piece (excluding packing) 627.100 g
Custom tariff number 85444290
Country of origin DE (Germany)
General
Nominal voltage UN < 50 V AC
60 V DC
Max. current carrying capacity per path 1 A

Max. total current of all branches 2 A
Max. conductor resistance 0.16 ?/m
Length of cable 3 m
Single wire, cross section 0.14 mm²
Single wire, cross section [AWG] 26
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
Shielding no
Outer sheath, material PVC
External sheath, color RAL7035
Environmental conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Flame resistance IEC 60332-1
DIN VDE 0482 Part 332-1
Resistance to oil DIN VDE 0472 Part 803, test type B
Gasoline resistance against occasional splashes
Connector 1
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 4
Number of positions 14
Pitch 2.54 mm
Connector 2
Connection name Controller level
Connection method Fujitsu connector
Number of connections 1
Number of positions 40
Supported controller
Controller MITSUBISHI MELSEC Q
- suitable I/O card QX41
QX41-S1
QX42
QX42-S1
QY41P
QY42P
QH42P
QY82P
Controller MITSUBISHI MELSEC L
- suitable I/O card LX41C4
LX42C4
LY41NT1P
LY42NT1P
LY41PT1P
LY42PT1P
Controller Honeywell MasterLogic 200
- suitable I/O card 2MLQ-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-FCN40/4X14/ 3,0M/IM/MEL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.