INDUSTRIAL COMPONENT DATA

CN-LAMBDA/4-5.9-SB 2800023 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: CN-LAMBDA/4-5.9-SB



Manufacturer	PHOENIX CONTACT
MPN / Reference	CN-LAMBDA/4-5.9-SB
Catalog number	2800023
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-58BA4DBE54
Generated	2026-11-18

Product Overview

Surge protection device
Adapter with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: N male-female connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2800023
Packing unit 1 pc
Catalog page Page 179 (C-4-2017)
GTIN 4046356410083
Weight per Piece (excluding packing) 187.800 g
Custom tariff number 85363010
Country of origin US (United States)
Dimensions
Height 38 mm
Width 26.1 mm
Depth 65 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C

Degree of protection IP68
General
Housing material Brass (CuZn)
Color nickel
Mounting type Connection-specific intermediate plugging
Type Attachment plug
Direction of action Line-Shield/Earth Ground
Protective circuit
IEC test classification C2
C3
D1
VDE requirement class C2
C3
D1
Rated current 5 A (25 °C)
Nominal discharge current In(8/20) µs (line-earth) 50 kA
Nominal discharge current In(8/20) µs (line-shield) 50 kA
Pulse discharge current Iimp(10/350) µs <= 20 kA
Total discharge current Itotal(8/20) µs 60 kA
Total discharge current Itotal(10/350) µs 20 kA
Max. discharge current Imax(8/20) µs maximum (line-earth) 60 kA
Max. discharge current Imax(8/20) µs maximum (line-shield) 60 kA
Output voltage limitation at 1 kV/µs (line-earth) spike <= 11 V (6 kV / 3 kA)
Output voltage limitation at 1 kV/µs (line-shield) spike <= 11 V (6 kV / 3 kA)
Output voltage limitation at 1 kV/µs (line-earth) static <= 11 V (6 kV / 3 kA)
Output voltage limitation at 1 kV/µs (line-shield) static <= 11 V (6 kV / 3 kA)
Voltage protection level Up(line-earth) <= 11 V (6 kV / 3 kA)
Voltage protection level Up(line-shield) <= 11 V (6 kV / 3 kA)
Input attenuation aE, asym. typ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CN-LAMBDA/4-5.9-SB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.