

INDUSTRIAL COMPONENT DATA

AX OPC SERVER 2985945 PHOENIX CONTACT Software

Brand: PHOENIX CONTACT | Manufacturer Part Number: AX OPC SERVER



Manufacturer	PHOENIX CONTACT
MPN / Reference	AX OPC SERVER
Catalog number	2985945
Category	Visualization software
Minimum order	1 Pcs
Document ID	EO-7693957539
Generated	2026-09-19

Product Overview

Software

AX OPC SERVER, communication interface for visualization suitable for OPC, with WORX PC-based control systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Automation Software (AS)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 2985945

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 67 (C-6-2017)

GTIN 4046356103497

Weight per Piece (excluding packing) 81.000 g

Custom tariff number 85234910

Country of origin DE (Germany)

License information

Intended use for the software Runtime license

Type of license Single-user license

Information regarding the version Valid for Version 3.09x (for features of older versions, please refer to the version information in the download area)

The versions of devices, other software packages or the operating system must be kept up to date.

Functions

Basic functions Supports OPC standard functions and all the optional interfaces (in accordance with OPC spec. DA 1.0a and DA 2.04/2.05)

Simultaneous support to several controllers

Integrated OPC testing and diagnostics client

System limits 64 Ethernet connections

Supported controllers ILC 1xx, AXC 1xxx, ILC 3xx, AXC 3xxx, RFC 4xx, PC WORX RT BASIC/SRT

Number of supported controllers max. 64

Number of OPC items max. 20000 (active OPC tags, arrays and structures count as 1 item)

4500 (active OPC tags per controller; arrays and structures count as 1 item)

Supported data types (standard) BOOL, BYTE, INT, DINT, UINT, SINT, USINT, UDINT, WORD, DWORD, REAL, LREAL, STRING, TIME according to IEC 61709

Supported data types (user-defined) ARRAY OF, STRUCTS, ARRAY OF STRUCT, STRUCT in STRUCT according to IEC 61131

Hardware requirements

Hard disk min. 2 GByte

RAM min. 1 GByte (2 GB for W...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AX OPC SERVER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.