INDUSTRIAL COMPONENT DATA

AXC F 2152 STARTERKIT 1046568 PHOENIX CONTACT Starter kit

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXC F 2152 STARTERKIT



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXC F 2152 STARTERKIT
Catalog number	1046568
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-A510485B16
Generated	2026-11-18

Product Overview

Starter kit
AXC F 2152 starter kit including PLCnext Control AXC F 2152, voltage switch, digital input and output module, analog input and output module, potentiometer, switch module, PROFICLOUD license and power supply, patch cable, country connectors and documentation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Key Commercial Data
Orderkey 1046568
Packing unit 1 pc
GTIN 4055626641782
Weight per Piece (excluding packing) 2,087.000 g
Custom tariff number 85371091
Country of origin DE (Germany)
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Articles in set
PLCnext Control for the direct control of Axioline F I/Os. With two Ethernet interfaces. Complete with connector and bus

base module.
Axioline F, Digital I/O module, Digital inputs: 8, 24 V DC, connection method: 1-wire, Digital outputs: 8, 24 V DC, 500 mA, connection method: 1-wire, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connectors
Axioline F, Analog I/O module, Analog inputs: 2, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, connection method: 2-wire, Analog outputs: 2, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, connection method: 2-wire, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connectors
Runtime license for using devices in the PROFICLOUD, credit: 8760 units
Patch cable, CAT5, assembled, 2 m
VARIOFACE switch module, with COMBICON connector, for simulation, for 8 signals, for mounting DIN rail NS 35
Classifications
eCl@ss 5.127242207eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXC F 2152 STARTERKIT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.