

INDUSTRIAL COMPONENT DATA

AXC F XT ETH 1TX 2403115 PHOENIX CONTACT

Left-alignable Ethernet interface, for connection to a compatible m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXC F XT ETH 1TX



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXC F XT ETH 1TX
Catalog number	2403115
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-56E45C1A24
Generated	2026-09-21

Product Overview

Left-alignable Ethernet interface, for connection to a compatible modular controller from the PLCnext Control range.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Key Commercial Data

Orderkey 2403115

Packing unit 1 pc

Catalog page Page 13 (C-6-2019)

GTIN 4055626257433

Weight per Piece (excluding packing) 160.000 g

Custom tariff number 85176200

Country of origin DE (Germany)

Drawings

Ambient conditions

General

Inline potentials

Standards and Regulations

Classifications

Dimensions

Connection data

Data interfaces

Axioline potentials

Environmental Product Compliance

Drawings

Dimensional drawing

[Back to top](#)Dimensions

Dimensional drawing

Width 35 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (up to 2000 m above sea level)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (according to DIN EN 61131-2)

Permissible humidity (storage/transport) 5 % ... 95 % (according to DIN EN 61131-2)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 58 kPa ... 106 kPa (up to 4500 m above mean sea level)

Degree of protection IP20

[Back to top](#)Connection data

Designation Axioline F connector

Connection method Push-in connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Stripping length 8 mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXC F XT ETH 1TX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.