

INDUSTRIAL COMPONENT DATA

AXC F XT IB 2403018 PHOENIX CONTACT Left-alignable INTERBUS master, for the connection of INTERBUS remote bu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXC F XT IB



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXC F XT IB
Catalog number	2403018
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-0F37AC3189
Generated	2026-09-22

Product Overview

Left-alignable INTERBUS master, for the connection of INTERBUS remote bus components to a compatible modular controller from the PLCnext Control range.

Left-aligned INTERBUS master for connecting INTERBUS remote bus components to a compatible modular control system from the PLCnext Control series.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Key Commercial Data

Orderkey 2403018

Packing unit 1 pc

GTIN 4055626345819

Weight per Piece (excluding packing) 180.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Drawings

Ambient conditions

General

Axioline potentials

Environmental Product Compliance

Dimensions

Connection data

Data interfaces

Standards and Regulations

Classifications

Drawings

Dimensional drawing

[Back to top](#)Dimensions

Dimensional drawing

Width 35 mm

Height 126.1 mm

Depth 54 mm

Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (up to 2000 m above sea level)

-25 °C ... 55 °C (2000 m above sea level ... 3000 m above sea level)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level (at an operating temperature of up to 55°C, maximum))

Air pressure (storage/transport) 58 kPa ... 106 kPa (up to 4500 m above mean sea level)

Degree of protection IP20

[Back to top](#)Connection data

Designation Axioline F connector

Connection method Push-in connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXC F XT IB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.