INDUSTRIAL COMPONENT DATA

AXL F AI4 U XC 1H 2702008 PHOENIX CONTACT I/O module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F AI4 U XC 1H



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F AI4 U XC 1H
Catalog number	2702008
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-3C6D389E26
Generated	2026-11-18

Product Overview

I/O module
AxiolineF, Analog Input Module, Analog Inputs: 4, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, connection technology: 2, 3, 4 conductors, transmission rate on the local bus: 100 MBit/s, integrated sensor power supply, Extreme Conditions variant, protection rating: IP20, incl. bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2702008
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 115 (C-6-2017)
GTIN 4055626008400
Weight per Piece (excluding packing) 215.000 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Dimensional drawing

Width 35 mm
Height 126.1 mm
Depth 54 mm
Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C (Standard)
-40 °C ... 70 °C (Extended, see section “Tested successfully: use under extreme ambient conditions” in the data sheet.)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
Connection data
Designation Axioline F connector
Connection method Push-in connection
Note on the connection method Please observe the information provided on conductor cross sections in the “Axioline F: system and installation” user manual.
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F AI4 U XC 1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.