INDUSTRIAL COMPONENT DATA

AXL F DO16/3 XC 2F 2701228 PHOENIX CONTACT I/O module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F DO16/3 XC 2F



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F DO16/3 XC 2F
Catalog number	2701228
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-2BF9E1BE1B
Generated	2026-11-19

Product Overview

I/O module
AxiolineF, Digital output module, Digital outputs:16, 24 VDC, 500 mA, connection technology:3 conductors, Extreme Condition variant, transmission speed on the local bus:100 MBit/s, protection index: IP20, including bus socket module and AxiolineF connectors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2701228
Packing unit 1 pc
Catalog page Page 109 (C-6-2017)
GTIN 4046356730365
Weight per Piece (excluding packing) 308.400 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Dimensional drawing
Width 53.6 mm

Height 129.9 mm
Depth 54 mm
Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C (Standard)
-40 °C ... 70 °C (Extended, see section “Tested successfully: use under extreme ambient conditions” in the data sheet.)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
Connection data
Designation Axioline F connector
Connection method Push-in connection
Note on the connection method Please observe the information provided on conductor cross sections in the “Axioline F: system and installation” user manual.
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F DO16/3 XC 2F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.