INDUSTRIAL COMPONENT DATA

AXL E PB DI16 M12 6P 2701498 PHOENIX CONTACT Distributed I/O device

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL E PB DI16 M12 6P



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL E PB DI16 M12 6P
Catalog number	2701498
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-AEB039973E
Generated	2026-11-18

Product Overview

Distributed I/O device
AxiolineE, Digital input equipment, PROFIBUS DP, M12 quick connect technology, Digital inputs: 16, 24 VDC, connection technology: 4 conductors, Plastic housing, protection index: IP65/IP67

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2701498
Packing unit 1 pc
Catalog page Page 202 (C-6-2017)
GTIN 4046356763523
Weight per Piece (excluding packing) 480.000 g
Custom tariff number 85176200
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Dimensional drawing
Width 60 mm

Height 185 mm
Depth 30.5 mm
Note on dimensions The height is 212 mm including fixing clips.
Drill hole spacing 198.5 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -25 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 %
Permissible humidity (storage/transport) 5 % ... 95 %
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP65/IP67
General
Housing material Pocan®
Mounting type Wall mounting
Net weight 480 g
Interfaces
Designation PROFIBUS DP
No. of channels 2
Connection method M12 fast connection technology
Note on the connection method B-coded
Designation connection point Copper cable
Transmission speed 9.6 kbps ... 12 Mbps (Automatic baud rate detection)
Transmission physics PROFIBUS-DP-compliant copper cable
Address area assignment 1 ... 126, adjustable
Number of positions 5
System limits of the bus coupler
Designation PROFIBUS DP
Equipment type PROFIBUS slave
System-specific protocols PROFIBUS protocols DP V1
Supply
Desi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL E PB DI16 M12 6P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.