
INDUSTRIAL COMPONENT DATA

AXL F PWR 1H 2688297 PHOENIX CONTACT Power module

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL F PWR 1H



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL F PWR 1H
Catalog number	2688297
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-BC2099C39A
Generated	2026-11-19

Product Overview

Power module
AxiolineF, Feedback module for Ubus logic feed, max. 4 A, protection rating: IP20, incl. bus base module and AxiolineF connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2688297
Packing unit 1 pc
Catalog page Page 105 (C-6-2017)
GTIN 4046356566209
Weight per Piece (excluding packing) 107.000 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Dimensional drawing
Width 35 mm
Height 126.1 mm

Depth 54 mm
Note on dimensions The depth is valid when a TH 35-7,5 DIN rail is used (according to EN 60715).
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
Connection data
Designation Axioline F connector
Connection method Push-in connection
Note on the connection method Please observe the information provided on conductor cross sections in the “Axioline F: system and installation” user manual.
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Stripping length 8 mm
General
Mounting type DIN rail
Net weight 107 g
Note on....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL F PWR 1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.