INDUSTRIAL COMPONENT DATA

AXL SE PD8/8 24V/GND 1337225 PHOENIX CONTACT Axioline Smart Elements, Potential Distribution Module, 24 V DC..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL SE PD8/8 24V/GND



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL SE PD8/8 24V/GND
Catalog number	1337225
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-2A586DBA8F
Generated	2026-11-19

Product Overview

Axioline Smart Elements, Potential Distribution Module, 24 V DC, GND, IP20 protection rating
Axioline SmartElements, Potential Distribution Module, 24VDC, GND, Protection Index: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Technical datadimensionsDimensioned Drawing
width 14.9 mm
height 62.2 mm
Depth 62 mm
InterfacesSmart Element-Interface
Number of interfaces 1
Link Card Edge Connectors
Transmission speed See the system where you are using the Smart Element.
System FeaturesForm
ID code (hexadecimal) none
Process data channel 0 Bit
Input address range 0 Bytes (all systems except PROFIBUS)
1 Byte (PROFIBUS)
Output address range 0 Bytes

Need for parameterization data 1 Byte
Need configuration data 6 Bytes
Article featurestype modularity
Product Type I/O Components
Product Family Axioline Smart Elements
Installation Location See the system where you are using the Smart Element.
Insulation characteristics
Overvoltage Category II (IEC 60664-1, EN 60664-1)
Degree of pollution 2 (IEC 60664-1, EN 60664-1)
Electrical characteristicsPotentials: Smart Elements Logic Power Supply (UIF)
Power supply voltage via Card Edge connectors
Potentials: Periphery Power Supply (UP)
Power supply voltage 24 V DC (via Card Edge connectors)
Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current consumption max. 4 A
Current consumption Min. 9 mA (without peripherals attached)
Input max. 120 W (of which 1.06 W internal losses)
Min. 173 mW
Protection Circuit Prot. against overvoltages; See the system where you are using the Smart Element.
Prot. reverse polarity; Diode against inv. polarity
short-circuit/overload protection; Electronic fuse (for connection points 0 ... 7, 4 A)
Galvani...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL SE PD8/8 24V/GND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.