INDUSTRIAL COMPONENT DATA

# PT 1X2-BE/FM 2920010 PHOENIX CONTACT Type 2 surge protection base element

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1X2-BE/FM**




| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PT 1X2-BE/FM |
| Catalog number | 2920010 |
| Category | Surge protection device for data networks/MCR-technology |
| Minimum order | 1 Pcs |
| Document ID | EO-3FF6412A01 |
| Generated | 2026-11-18 |

## Product Overview

Type 2 surge protection base element
Base element for housing a plug-in protection with status indication for a two-wire circuit without earth potential

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Trabtech (TT) |

## Additional Product Information

Key Commercial Data
Orderkey 2920010
Packing unit 10 pc
Catalog page Page 90 (TT-2011)
GTIN 4046356154024
Weight per Piece (excluding packing) 51.060 g
Custom tariff number 85371098
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Height 89.8 mm
Width 17.7 mm
Depth 52 mm

Horizontal pitch 1 Div.
Complete module height 90 mm
Complete module width 17.7 mm
Complete module depth 65.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Degree of protection IP20
General
Flammability rating according to UL 94 V-0
Color black
Mounting type DIN rail: 35 mm
Type Base element, DIN rail mounting
Number of positions 2
Direction of action Shield-Earth Ground
Connection data
Connection method Screw connection
Connection method IN Screw terminal blocks
Connection method OUT Screw terminal blocks
Screw thread M3
Tightening torque 0.8 Nm
Stripping length 8 mm
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section AWG 24 ... 12
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140201eCl@ss 4.127130801eCl@ss 5.027130801eCl@ss 5.127130800eCl@ss 6.027130800eCl@ss 7.027130803eCl@ss 8.027130803eCl@ss 9.027130803
ETIM 2.0EC000472ETIM 3.0EC000472ETIM 4.0EC0004...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1X2-BE/FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.