INDUSTRIAL COMPONENT DATA

BC 161,6 OT 121222 BK VPE80 1059320 PHOENIX CONTACT DIN rail housing for use in distribution boards in accor..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6 OT 121222 BK VPE80



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 161,6 OT 121222 BK VPE80
Catalog number	1059320
Category	Extruded profile modular housing
Minimum order	480 Pcs
Document ID	EO-5D68074590
Generated	2026-11-19

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)
Rail box for use in installation distributors according to DIN 43880, Modular housing top, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1059320
Packing unit 1 pc
Minimum order quantity 480 pc
GTIN 4055626701592
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85389099
Country of origin DE (Germany)
Drawings
Dimensions
Ambient conditions
General information

Standards and regulations
Item properties
Material data
PCB data
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Upper part of housing
Type BC 161,6 OT 121222 BK VPE80
Order No. 1059320
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Back to topDimensions
Dimensional drawing
Width [w] 161.6 mm
Height [h] 89.7 mm
Depth [d] 54.85 mm
Back to topMaterial data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
PCB thickness 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6 OT 121222 BK VPE80 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.