
INDUSTRIAL COMPONENT DATA

BC 161,6 OT 220222 KMGY MOQ100 1126202 PHOENIX CONTACT DIN rail housing for use in distribution boards in ac..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6 OT 220222 KMGY MOQ100



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 161,6 OT 220222 KMGY MOQ100
Catalog number	1126202
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-8F77981AB4
Generated	2026-11-19

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)
Rail box for use in installation distributors according to DIN 43880, Top of the modular housing, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1126202
Packing unit 1
GTIN 4063151053581
Custom tariff number 85389099
Drawings
Dimensions
Ambient conditions
General information
Standards and regulations

Item properties
Material data
PCB data
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Upper part of housing
Type BC 161,6 OT 220222 KMGY MOQ100
Order No. 1126202
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Back to topDimensions
Dimensional drawing
Width [w] 161.6 mm
Height [h] 89.7 mm
Depth [d] 54.85 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
PCB thickness 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Type of packaging packed in cardboard
Pieces per package 10
Denomina...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6 OT 220222 KMGY MOQ100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.