
INDUSTRIAL COMPONENT DATA

BC 161,6 OT U11 KMGY S1193 1054283 PHOENIX CONTACT DIN rail housing for use in distribution boards in accord..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6 OT U11 KMGY S1193



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 161,6 OT U11 KMGY S1193
Catalog number	1054283
Category	Electronic enclosure
Minimum order	250 Pcs
Document ID	EO-998C72AEFE
Generated	2026-11-19

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)
Rail box for use in installation distributors according to DIN 43880, Top of the housing (U11) with ventilation slits, Installation depth of connection technology: 11.1 mm, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1054283
Packing unit 1
GTIN 4055626689319
Custom tariff number 85472000
Drawings
Dimensions
Ambient conditions
Packaging information
Classifications
Item properties
Material data

PCB data
Standards and regulations
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Upper part of housing
Type BC 161,6 OT U11 KMGY S1193
Order No. 1054283
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series BC
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Max. number of positions 96 (pitch: 2.5 mm)
72 (pitch: 3.5 mm)
54 (pitch: 5 mm)
36 (pitch: 7.5 mm)
Back to topDimensions
Dimensional drawing
Width [w] 161.6 mm
Height [h] 89.7 mm
Depth [d] 54.85 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
Number of PCB holders 18
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topPackaging information
Type of packaging packed in cardboard
Pieces per package 10
Denomination packing units Pcs.
Outer pack...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6 OT U11 KMGY S1193 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.