INDUSTRIAL COMPONENT DATA

# BC 71,6 OT 0201 KMGY 1091777 PHOENIX CONTACT DIN rail housing for use in distribution boards in accordance w..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 0201 KMGY**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | BC 71,6 OT 0201 KMGY |
| Catalog number | 1091777 |
| Category | Extruded profile modular housing |
| Minimum order | 250 Pcs |
| Document ID | EO-C50132361B |
| Generated | 2026-11-19 |

## Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm
Rail housing for use in installation distributors according to DIN 43880, Top of modular housing, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 1091777
Packing unit 1
GTIN 4055626906201
Custom tariff number 85389099
Item properties
Material data
PCB data
Standards and regulations
Dimensions
Ambient conditions
Packaging information

Classifications
Item properties
Brief article description Upper part of housing
Type BC 71,6 OT 0201 KMGY
Order No. 1091777
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series BC
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Max. number of positions 44 (pitch: 2.5 mm)
32 (pitch: 3.5 mm)
24 (pitch: 5 mm)
16 (pitch: 7.5 mm)
Back to topDimensions
Width [ w ] 71.6 mm
Height [ h ] 89.7 mm
Depth [ d ] 54.85 mm
Back to topMaterial data
Color (RAL) light gray
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
Number of PCB holders 1
PCB thickness 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topPackaging information
Pieces per package 20
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@s...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 0201 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.