
INDUSTRIAL COMPONENT DATA

BC 71,6 OT 1010 KMGY MOQ100 1136628 PHOENIX CONTACT DIN rail housing for use in distribution boards in accor..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 1010 KMGY MOQ100



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 71,6 OT 1010 KMGY MOQ100
Catalog number	1136628
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-93D44538C8
Generated	2026-11-19

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)
Rail housing for use in installation distributors according to DIN 43880, Top of modular housing, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1136628
Packing unit 1
GTIN 4063151073190
Custom tariff number 85389099
Drawings
Dimensions
Ambient conditions
General information
Standards and regulations
Item properties
Material data

PCB data
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Upper part of housing
Type BC 71,6 OT 1010 KMGY MOQ100
Order No. 1136628
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series BC
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Max. number of positions 44 (pitch: 2.5 mm)
32 (pitch: 3.5 mm)
24 (pitch: 5 mm)
16 (pitch: 7.5 mm)
Back to topDimensions
Dimensional drawing
Width [w] 71.6 mm
Height [h] 89.7 mm
Depth [d] 54.85 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
Number of PCB holders 1
PCB thickness 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 1010 KMGY MOQ100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.