
INDUSTRIAL COMPONENT DATA

BC 71,6 OT 2101 KMGY 1016754 PHOENIX CONTACT DIN rail housing for use in distribution boards in accordance w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 2101 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 71,6 OT 2101 KMGY
Catalog number	1016754
Category	Electronic enclosure
Minimum order	100 Pcs
Document ID	EO-D9615757BA
Generated	2026-11-19

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1016754
Packing unit 1
GTIN 4055626820903
Custom tariff number 85389099
Item properties
Material data
PCB data
Standards and regulations
Dimensions
Ambient conditions
Packaging information
Classifications
Item properties

Brief article description Upper part of housing
Type BC 71,6 OT 2101 KMGY
Order No. 1016754
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series BC
Type Upper housing part with vents
Max. IP code to attain IP20
Mounting type Snap in
Connection levels 1 (Both sides)
Ventilation openings present yes
Max. number of positions 44 (pitch: 2.5 mm)
32 (pitch: 3.5 mm)
24 (pitch: 5 mm)
16 (pitch: 7.5 mm)
Back to topDimensions
Width [w] 71.6 mm
Height [h] 89.7 mm
Depth [d] 54.85 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB data
Number of PCB holders 1
PCB thickness 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Latching
Back to topPackaging information
Pieces per package 20
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 2101 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.