
INDUSTRIAL COMPONENT DATA

BCH-350V- 5 GN 5441304 PHOENIX CONTACT Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. º p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-350V-5 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-350V-5 GN
Catalog number	5441304
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-D19852AA87
Generated	2026-11-19

Product Overview

Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. º poles: 5,Pitch: 3.5 mm,Color: whitish green,contact Surface: Tin,Assembly: wave Soldering
Printed circuit board base housing, nominal section: 1.5 mm², color: whitish green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, article family: BCH-V, pitch: 3.5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed
PCB base socket, nominal cross-section: 1.5 mm2, colour: white green, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: plug, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, product series: BCH-V, pitch: 3.5 mm, mounting: wave soldering, Pin layout: Linear pinning, pin length [P]: 3.4 mm, number of solder pins per potential: 1, pin system: BASICLINE 1.5, Insertion pin orientation: Standard, locking: none, fastening type: none, packaging type: carton-packed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5441304
Packing unit 100 pc
Minimum order quantity 100 pc

GTIN 4046356524018
Weight per Piece (excluding packing) 0.890 g
Custom tariff number 85366930
Country of origin CN (China)
Dimensions
Length [l] 7.4 mm
Width 18.9 mm
Pitch 3.5 mm
Dimension a 14 mm
Width [w] 18.9 mm
Height [h] 12.6 mm
Height 9.2 mm
Length of the solder pin 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Length 7.4 mm
General
Range of articles BCH-V
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Color pastel green
Number of positions 5
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-350V-5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.