INDUSTRIAL COMPONENT DATA

BCH-381HF-12 BK 5452342 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-381HF-12 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-381HF-12 BK
Catalog number	5452342
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-0544CEBBB8
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: BCH-HF, pitch: 3.81 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: Screw lock, fastening type: Overhead clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5452342
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4046356852395
Weight per Piece (excluding packing) 3.710 g
Custom tariff number 85366930
Country of origin CN (China)
Dimensions

Length [l] 9.2 mm
Width 56.11 mm
Pitch 3.81 mm
Dimension a 41.91 mm
Width [w] 56.11 mm
Height [h] 10.55 mm
Height 7.15 mm
Length of the solder pin 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Length 9.2 mm
General
Range of articles BCH-HF
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Color black
Number of positions 12
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121409UNS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-381HF-12 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.