INDUSTRIAL COMPONENT DATA

BCH-500H-20 BK 5452285 PHOENIX CONTACT Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. º ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500H-20 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500H-20 BK
Catalog number	5452285
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-879AEAB9A8
Generated	2026-11-19

Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. º poles: 20,Pitch: 5 mm,Color: black,contact Surface: Tin,Assembly: wave Soldering
Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact connection type: Male, number of potentials: 20, number of rows: 1, number of poles: 20, number of connections: 20, article family: BCH-H, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Data commercial
Key order Five million four hundred fifty two thousand two hundred eighty five
Packing unit 100 pcs
Key selling AAYBFA -
Minimum order quantity 100 pcs
EAN Four trillion forty six billion three hundred fifty six million eight hundred fifty two thousand nine hundred sixty eight
Unit weight (excluding packaging) 7,400 g
Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety
Country of origin CN (China)

Dimensions
Length [l] 12 mm
Width 100 mm
Step 5 mm
Average 95 mm
Width [w] 100 mm
Height [h] 12 mm
Height of construction 8.6 mm
Length of the pin welding 3.4 mm
Dimensions of pin 1 x 1 mm
Length 12 mm
Overview
Family of articles BCH-H
Group insulating material I
Transient voltage design (III/3) 4 kV
Transient voltage design (III/2) 4 kV
Transient voltage design (II/2) 4 kV
Tension and sizing (III/3) 250 V
Tension and sizing (III/2) 320 V
Tension and sizing (II/2) 400 V
Connection according to standard EN-VDE
Nominal current IN 12 To
Maximum load current 12 To
Isolation PA
Class of flammability according to UL 94 V0
Color black
Number of poles Twenty
Standards and specifications
Connection according to standard EN-VDE
CUL
Class of flammability according to UL 94 V0
Environmental Product Compliance
China RoHS Space of time for the intended use: unlimited = FEUP-e
No dangerous substances above the thresholds
Ratings
eCl@ss 4.0272607xxeCl@ss 4.1Twenty seven million two hundred sixty thousand seven hundred oneeCl@ss 5.0Twe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500H-20 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.