INDUSTRIAL COMPONENT DATA

BCH-500HS- 2 GN 5441197 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500HS-2 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500HS-2 GN
Catalog number	5441197
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-190C8BABF1
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: whitish green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: BCH-HS, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5441197
Packing unit 100 pc
Minimum order quantity 100 pc
GTIN 4046356523899
Weight per Piece (excluding packing) 1.030 g
Custom tariff number 85366930
Country of origin CN (China)
Dimensions
Length [l] 12 mm

Width 12 mm
Pitch 5 mm
Dimension a 5 mm
Width [w] 12 mm
Height [h] 12.07 mm
Height 8.57 mm
Length of the solder pin 3.5 mm
Pin dimensions 1 x 1 mm
Length 12 mm
General
Range of articles BCH-HS
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Maximum load current 12 A
Insulating material PA
Flammability rating according to UL 94 V0
Color pastel green
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500HS-2 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.