INDUSTRIAL COMPONENT DATA

BCH-500VF- 3 GN 5445902 PHOENIX CONTACT Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. º..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500VF-3 GN

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500VF-3 GN
Catalog number	5445902
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-CD8F81C295
Generated	2026-11-19

Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. º poles: 3,Pitch: 5 mm,Color: whitish green,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: whitish green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, article family: BCH-VF, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: Screw lock, fastening type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500VF-3 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.