INDUSTRIAL COMPONENT DATA

BCH-508HS- 3 GY PA1,3 1039174 PHOENIX CONTACT Housing base for printed circuit board, number of poles: 3, pi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-508HS-3 GY PA1,3



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-508HS-3 GY PA1,3
Catalog number	1039174
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-014D8D165E
Generated	2026-11-19

Product Overview

Housing base for printed circuit board, number of poles: 3, pitch: 5,08 mm, color: gray signals, surface of contact: Tin, assembly: wave Soldering
Printed circuit board base housing, nominal section: 2.5 mm², color: signal gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 3, number of connections: 2, article family: BCH-HS, pitch: 5.08 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1039174
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4055626592121
Weight per Piece (excluding packing) 1.390 g
Custom tariff number 85366930
Country of origin CN (China)

Dimensions
Length [l] 12 mm
Width 17.24 mm
Pitch 5.08 mm
Dimension a 10.16 mm
Width [w] 17.24 mm
Height [h] 12.07 mm
Height 8.57 mm
Length of the solder pin 3.5 mm
Pin dimensions 1 x 1 mm
Length 12 mm
General
Range of articles BCH-HS
Color signal grey
Number of positions 3
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 5.0EC002637ETIM 6.0EC002637

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-508HS-3 GY PA1,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.