INDUSTRIAL COMPONENT DATA

BCH-508VS-23 BK 5452174 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-508VS-23 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-508VS-23 BK
Catalog number	5452174
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-3A5AC2E545
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 23, number of rows: 1, number of poles: 23, number of connections: 23, family of articles: BCH-VS, pitch: 5.08 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5452174
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4046356854078
Weight per Piece (excluding packing) 9.000 g
Custom tariff number 85366930
Country of origin CN (China)
Dimensions

Length [l] 8.6 mm
Width 118.84 mm
Pitch 5.08 mm
Dimension a 111.76 mm
Width [w] 118.84 mm
Height [h] 15.9 mm
Height 12 mm
Length of the solder pin 3.9 mm
Pin dimensions 1 x 1 mm
Length 8.6 mm
General
Range of articles BCH-VS
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Maximum load current 12 A
Insulating material PA
Flammability rating according to UL 94 V0
Color black
Number of positions 23
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-508VS-23 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.