INDUSTRIAL COMPONENT DATA

BCP-350- 3 GY BD:13-15 5454537 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-350- 3 GY BD:13-15



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-350- 3 GY BD:13-15
Catalog number	5454537
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-572A9368C0
Generated	2026-11-19

Product Overview

PCB connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5454537
Packing unit 100 pc
Minimum order quantity 500 pc
Note Made to Order (non-returnable)
GTIN 4046356982856
Weight per Piece (excluding packing) 2.230 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Length [l] 16.1 mm
Width [w] 11.2 mm
Height [h] 11.1 mm
Pitch 3.5 mm
Dimension a 7 mm

General
Range of articles BCP
Number of positions 3
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 0.5 mm²
2 conductors with same cross section, stranded min. 0.25 mm²
2 conductors with same cross section, stranded max. 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-350- 3 GY BD:13-15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.