INDUSTRIAL COMPONENT DATA

BCP-381F- 4 GN 5448077 PHOENIX CONTACT Part plug,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. º pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-381F-4 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-381F-4 GN
Catalog number	5448077
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-D3333661D6
Generated	2026-11-18

Product Overview

Part plug,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. º poles: 4,Pitch: 3,81 mm,the Technique of connection: Connection by screw with capsule-traction,Color: whitish green,contact Surface: Tin
Connector for printed circuit board, nominal cross-section: 1.5 mm², color: off-white, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: BCP-F, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, conductor/printed circuit board connection direction: 0 °, plug-in system: BASICLINE 1.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed
PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 4, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: pastel green, contact surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 5448077
Packing unit 1 pc
Minimum order quantity 100 pc
GTIN 4046356837712
Weight per Piece (excluding packing) 4.000 g
Custom tariff number 85366990

Country of origin CN (China)
Drawings
General
Standards and Regulations
Classifications
Dimensions
Connection data
Environmental Product Compliance
Drawings
Diagram
Dimensional drawing
Back to topDimensions
Length [l] 16.1 mm
Width [w] 25.63 mm
Height [h] 11.1 mm
Pitch 3.81 mm
Dimension a 11.43 mm
Back to topGeneral
Range of articles BCP-F
Number of positions 4
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Maximum load current 8 A (with 1.5 mm² conductor cross section)
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A1
Stripping length 7 mm
Screw thread M2
Tightening torque, min 0.22 Nm
Tightening torque max 0.25 Nm
Back to topConnection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with fe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-381F-4 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.