INDUSTRIAL COMPONENT DATA

# BCP-508- 2 GY BD:R3A-R3C Q 5455659 PHOENIX CONTACT PCB connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508-2 GY BD:R3A-R3C Q**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | BCP-508-2 GY BD:R3A-R3C Q |
| Catalog number | 5455659 |
| Category | Cable connector |
| Minimum order | 100 Pcs |
| Document ID | EO-66503D269A |
| Generated | 2026-11-19 |

## Product Overview

PCB connector
Connector for printed circuit board, nominal section: 2.5 mm², color: gray signals, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: BCP, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 5455659
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4046356992572
Weight per Piece (excluding packing) 3.680 g
Custom tariff number 85366990
Country of origin CN (China)

Dimensions
Length [ l ] 18.2 mm
Width [ w ] 10.16 mm
Height [ h ] 15 mm
Pitch 5.08 mm
Dimension a 5.08 mm
General
Range of articles BCP
Number of positions 2
Connection method Screw connection with tension sleeve
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²
2 conductors with same cr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508-2 GY BD:R3A-R3C Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.