INDUSTRIAL COMPONENT DATA

HC-B 16-SMLD-67/M2M25 1586882 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-SMLD-67/M2M25



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-SMLD-67/M2M25
Catalog number	1586882
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-358002FB68
Generated	2026-11-18

Product Overview

Housing
Plinth housing, with longitudinal flange, height 67 mm, with cable gland, 2x M25, with protective cover

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1586882
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 573 (PC-2011)
GTIN 4046356426978
Weight per Piece (excluding packing) 416.500 g
Custom tariff number 85389099
Country of origin DE (Germany)
Dimensions
Height 67 mm
Width 57 mm
Length 117 mm
Wrench size, union nut 25 mm

External cable diameter 9 mm ... 18 mm (Cable 1)
9 mm ... 18 mm (Cable 2)
Ambient conditions
Degree of protection of housing (IP) IP65 (When plugged in)
IP54 (with closed protective cover)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
Size B16
Housing type Box mounting bases
Locking type with single locking latch
No. of cable outlets 2
Cable outlet lateral
Screw connection with
Type of the screw connection 2x M25
Protective cover yes
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Cable gland material Nickel-plated brass
Cable seal material NBR
Material lock Stainless steel, handle: PA
Material grip body interlock PA
Material, protective cover PA
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 6.013...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-SMLD-67/M2M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.