INDUSTRIAL COMPONENT DATA

HC-STA-B24-SLWSC-2SSP21-ELC-AL 1412883 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B24-SLWSC-2SSP21-ELC-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B24-SLWSC-2SSP21-ELC-AL
Catalog number	1412883
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-67AE050EA4
Generated	2026-11-19

Product Overview

Housing
B24 socket housing, with longitudinal flange, material: Injected cast aluminum, seawater resistant, protective cap material: PC, cable outlets: 2, side, 2x Pg21, height: 68 mm, cable gland: without, protective cover: yes, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1412883
Packing unit 1 pc
Catalog page Page 623 (C-2-2017)
GTIN 4055626061320
Weight per Piece (excluding packing) 380.000 g
Custom tariff number 85389099
Country of origin CN (China)
Dimensions
Height 68 mm
Width 57 mm
Length 144 mm
Ambient conditions

Degree of protection (IP) IP66 (with locked protective cover)
IP67 (when plugged in)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
Size B24
Housing type Box mounting bases
Color gray aluminum
Locking type with single locking latch
No. of cable outlets 2
Cable outlet lateral
Screw connection none
Type of the screw connection 2x Pg21
Protective cover yes
Housing material Die-cast aluminum, salt water resistant
Housing surface material uncoated
Seal material NBR, conductive
Material lock PA
Material, protective cover PA
Assembly instructions One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B24-SLWSC-2SSP21-ELC-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.