INDUSTRIAL COMPONENT DATA

HC-EVO-B10-SHFDC-2SSM32-PLRBK 1407639 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-EVO-B10-SHFDC-2SSM32-PLRBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-EVO-B10-SHFDC-2SSM32-PLRBK
Catalog number	1407639
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-7D4511A95E
Generated	2026-11-19

Product Overview

Housing
B10 socket housing, for cross flange, material: PA, protective cap material: PC, cable outlets: 2, side, 2x M32, height: 74 mm, cable gland: without, protective cover: yes, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1407639
Packing unit 1 pc
Catalog page Page 602 (C-2-2017)
GTIN 4046356777018
Weight per Piece (excluding packing) 156.300 g
Custom tariff number 85389099
Country of origin PL (Poland)
Dimensions
Height 74 mm
Width 57 mm
Length 93 mm
Ambient conditions

Degree of protection (IP) IP66 (when plugged in)
IP54 (with closed protective cover)
Degree of protection (NEMA) 12 (UL 50e)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3-E...C
Size B10
Housing type Box mounting bases
Color black
Locking type for double locking latch
No. of cable outlets 2
Cable outlet lateral
Screw connection none
Type of the screw connection 2x M32
Protective cover yes
Housing material PA
Seal material NBR
Material, protective cover PA
Flammability rating according to UL 94 V0
Connection One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 6.0131261502UNSPSC 7.090131261502UNSPSC 1131261502UNSPSC 12.013126150...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-EVO-B10-SHFDC-2SSM32-PLRBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.