INDUSTRIAL COMPONENT DATA

BSLK 16 0810012 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BSLK 16



Manufacturer	PHOENIX CONTACT
MPN / Reference	BSLK 16
Catalog number	0810012
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-3D150D4D06
Generated	2026-11-19

Product Overview

Ground modular terminal block
Ground terminal, number of connections: 2, number of poles: 1, type of connection: Screw connection, cross-section: 0.5 mm² - 16 mm², mounting class: NS 35/7.5, NS 35/15, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 0810012
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4017918007935
Weight per Piece (excluding packing) 13.340 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of positions 1
Number of levels 1
Number of connections 2
Color silver

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel Yes
Dimensions
Width 8 mm
Length 50 mm
Height NS 35/7,5 34 mm
Height NS 35/15 41.5 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 10 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 8
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²
2 conductors with same cross section, solid min. 0.5 mm²
2 conductors with same cross section, solid max. 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BSLK 16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.