INDUSTRIAL COMPONENT DATA

BT 1,25 3281122 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BT 1,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	BT 1,25
Catalog number	3281122
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-BA3135B013
Generated	2026-11-19

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 690 V, nominal current: 17.5 A, connection type: Annular cable terminal, number of connections: 2, width: 7 mm, color: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3281122
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 387 (C-1-2017)
GTIN 4055626118093
Weight per Piece (excluding packing) 6.530 g
Custom tariff number 85369010
Country of origin IN (India)
General
Number of levels 1
Number of connections 2

Potentials 1
Nominal cross section 1.5 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 0.56 W
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 17.5 A
Nominal current IN 17.5 A
Nominal voltage UN 690 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 1.5 mm² / 0.4 kg
Tensile test result Test passed
Conductor cross section tensile test 1.5 mm²
Tractive force setpoint 40 N
Conductor cross section tensile test 1.25 mm²
Tractive...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BT 1,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.