

INDUSTRIAL COMPONENT DATA

BTFE 6-3/14 AUX 1029253 PHOENIX CONTACT Test terminal strip, nom. voltage: 400 V, nominal current: 24 A, con..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTFE 6-3/14 AUX



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTFE 6-3/14 AUX
Catalog number	1029253
Category	(Knife) disconnect terminal block
Minimum order	1 Pcs
Document ID	EO-3BD9A19313
Generated	2026-09-21

Product Overview

Test terminal strip, nom. voltage: 400 V, nominal current: 24 A, connection method: Ring cable lug, color: gray, mounting type: Wall mounting

Test pin strip, rated voltage: 400 V, rated current: 24 A, connection type: Ring cable terminal, 1st floor, mounting class: Wall mount, color: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1029253

Packing unit 1

Catalog page Page 650 (C-1-2019)

GTIN 4055626531090

Custom tariff number 85366990

Drawings

Connection data

Standards and Regulations

Classifications

General

Mounting

Environmental Product Compliance

Drawings

Dimensional drawing

X = 123.9 mm

Y = 6.0 mm

Circuit diagram

[Back to top](#)General

Nominal cross section 4 mm²

Color gray

Insulating material PC

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Test surge voltage 5 kV

Overvoltage category III

Insulating material group I

Maximum load current 24 A

Nominal current I_N 24 A

Current I_{th} 24 A

Nominal voltage U_N 400 V

Open side panel No

[Back to top](#)Connection data

Connection 1 level

Connection method Ring cable lug

Tightening torque, min 1 Nm

Tightening torque max 1.3 Nm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 6 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 10

Cable lug connection according to standard DIN 46234:1980-03

Min. cross section for cable lug connection 0.5 mm²

Max. cross section for cable lug connection 6 mm²

Hole diameter, min. 3.7 mm

Cable lug width, max. 6.8 mm

Bolt diameter 3.5 mm

Cable lug connection according to standard DIN 46237:1970-07

Min. cross section for cable lug connection 0.5 mm²

Max. cross section for cable lug connection 6 mm²

Hole diameter, min. 3.7 mm

Cable lug width, max. 6.8 mm

Bolt diameter 3.5 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTFE 6-3/14 AUX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.