INDUSTRIAL COMPONENT DATA

BTP 3,5 3281116 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTP 3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTP 3,5
Catalog number	3281116
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-5A966B7F48
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, connection type: Push-in connection, number of connections: 4, cross-section: 0.2 mm² - 4 mm², AWG: 24 - 12, width: 10 mm, colour: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3281116
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 391 (C-1-2017)
GTIN 4055626119175
Weight per Piece (excluding packing) 11.320 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 1
Number of connections 4

Potentials 1
Nominal cross section 4 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 1.02 W
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 32 A (The maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal current IN 32 A
Nominal voltage UN 690 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTP 3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.