INDUSTRIAL COMPONENT DATA

SAC-5P-M 8MS/15,0-920/M 8FS 1575880 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M 8MS/15,0-920/M 8FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M 8MS/15,0-920/M 8FS
Catalog number	1575880
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-6F616A5AF5
Generated	2026-11-18

Product Overview

Bus system cable
Bus system cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, Straight M8 connector, encoding: B, a Straight female M8, cable length: 15 m, Unshielded plug-in connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1575880
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 432 (C-2-2017)
GTIN 4046356431569
Weight per Piece (excluding packing) 900.220 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 15 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Note Further products with variable cable lengths can be found in the accessories section
Rated current at 40°C 4 A
Rated voltage 30 V AC
30 V DC
Number of positions 5
Color handle area black
Insulation resistance >= 100 M?
Coding B - inverse
Signal type/category CANopen®
DeviceNet™
Status display No
Overvoltage category II
Degree of pollution 3
Torque 0.2 Nm (M8 connectors)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Pin assignment
Contact | Color (signal designation) | Contact (optional) 1 (Plug) | SR (shield) | 1 (Socket)
2 (Plug) | RD (V+) | 2 (Socket)
4 (Plug) | BK (V-) | 4 (Socket)
3 (Plug) | WH (CAN_H) | 3 (Socket)
5 (Plug) | BU (CAN_L) | 5 (Socket)
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type CAN Bus/DeviceNet
Cable type (abbreviation) 920
UL AWM style 21198 (80°C/300 V)
Cable structure 2xAWG24/19+2xAWG22/19
Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M 8MS/15,0-920/M 8FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.