INDUSTRIAL COMPONENT DATA

SAC-2P-10,0-910/M12FSB 1507311 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-10,0-910/M12FSB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-10,0-910/M12FSB
Catalog number	1507311
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5C7C10F3F9
Generated	2026-11-19

Product Overview

Bus system cable
Bus system cable, PROFIBUS (12 MBit/s), 2-pole halogen-free, shielded, free cable end, a Straight female M12, coding: B, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1507311
Packing unit 1 pc
Catalog page Page 429 (C-2-2017)
GTIN 4017918900144
Weight per Piece (excluding packing) 611.700 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 10 m
Stripping length of the free conductor end 50 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Note Further products with variable cable lengths can be found in the accessories section
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 2
Insulation resistance >= 100 M?
Coding B - inverse
Signal type/category PROFIBUS, 12 Mbps (max. 100 m)
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Pin assignment
Contact | Color (signal designation) | Contact (optional) 2 (Socket) | GN (A cable)
4 (Socket) | RD (B cable)
Cable
Cable type PROFIBUS
Cable type (abbreviation) 910
UL AWM style 21198 (80°C/300 V)
Cable structure 1x2xAWG24/19
Conductor cross section 2x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 19x 0.13 mm
Core diameter including insulation 2.55 mm ±0.07 mm
Wire colors Red, green
Overall twist 2 cores with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-10,0-910/M12FSB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.