

INDUSTRIAL COMPONENT DATA

C PX A 200X300X168 0899332 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: C PX A 200X300X168



Manufacturer	PHOENIX CONTACT
MPN / Reference	C PX A 200X300X168
Catalog number	0899332
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-96DBFD293E
Generated	2026-09-24

Product Overview

Junction box

Empty housing, material: Fiberglass reinforced polyester, with graphite supplement, black, 300 mm x 200 mm x 171 mm, lock type: Door, scope of delivery - ATD: Door hinge with 8 mm square closure, Door hinge with 8 mm square closure

Empty housing, material: polyester glass fibre reinforced, with graphite additive, black, 300 mm x 200 mm x 171 mm, locking type: door, scope of delivery - ATD: door hinge with 8 mm square lock, door hinge with 8 mm square lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 0899332

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 534 (C-3-2017)

GTIN 4055626276014

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 85389099

Country of origin HU (Hungary)

General

Type Ex empty enclosure with door

Note Mounting plate required

Scope of supply Door hinge with 8 mm square lock

Color black

Flammability rating according to UL 94 V0

Direct DIN rail mounting No

Useable DIN rail type NS 35

Dimensions

Width 300 mm

Height 200 mm

Depth 171 mm

Clearance width, maximum DIN rail length 251 mm

Assembly length, max. 231 mm

General

Housing material Glass-fiber-reinforced polyester with added graphite

Cover fastening Door

Note Square lock

Fixing device External fixing clips

External fixing clip not supplied as standard

Seal material Silicon

Components halogen-free

Ambient conditions

Degree of protection of housing (IP) IP66

Protection class II

Degree of protection (IK) 7.00 J EN 60079-0

Temperature in operating conditions -55 °C ... 127 °C

Standards and Regulations

Standards/regulations EN 60079-0

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127180190eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127180100eCl@ss

6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190

ETIM 3.0EC000897ETIM 4.0EC002498ETIM 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C PX A 200X300X168 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.