INDUSTRIAL COMPONENT DATA

CA-16P1NC22S00 1619907 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-16P1NC22S00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-16P1NC22S00
Catalog number	1619907
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-6E9FBAC4AC
Generated	2026-11-19

Product Overview

Device connector, front mounting
M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard and SPEEDCON locking, No. of poles: 16, Direction of rotation: Standard, type of contact: Male, Weld connection, Flat joint, 4x Ø 3.2, flange size: 25 mm x 25 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243885

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1619907
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356820608
Weight per Piece (excluding packing) 11.110 g
Custom tariff number 85366990
Country of origin DE (Germany)
Temperature range
Ambient temperature (operation) -40 °C ... 125 °C
Dimensions
free solder pin length 17.5 mm

Data of the insulating body
Coding N
Insulator material PBT
Contact material CuZn
Contact surface material Ni/Au
Contact connection method Solder-in connection
Type of contacts Pin
Application Signal
Number of positions 16
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Nominal voltage, power contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Housing material CuZn
Flange dimensions 25 mm x 25 mm
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC 13.2391...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-16P1NC22S00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.