INDUSTRIAL COMPONENT DATA

CA-1RS1N8A0000 1623626 PHOENIX CONTACT Insert contacts, number of poles: 16+2+PE, type of contact: Socket, C..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-1RS1N8A0000



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-1RS1N8A0000
Catalog number	1623626
Category	Contact insert for circular connectors
Minimum order	10 Pcs
Document ID	EO-140AC51F60
Generated	2026-11-19

Product Overview

Insert contacts, number of poles: 16+2+PE, type of contact: Socket, Connection set
Contact insert, M23, number of poles: 16+2+FE, contact type: Female, Crimped connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Insert contacts, number of poles: 16+2+PE, type of contact: Socket, Connection set
Data commercial
Key order One million six hundred twenty three thousand six hundred twenty six
Packing unit 10 pcs
Key selling ABRBFY -
Minimum order quantity 10 pcs
EAN Four trillion fifty five billion six hundred twenty six million one hundred seventy thousand five hundred eighty nine
Unit weight (excluding packaging) 2,440 g
Tariff number tariff Eighty five million four hundred seventy two thousand
Country of origin DE (Germany)
Overview
Observation Indication of order: The contacts crimpados 16 x Ø 1 mm, 3 x Ø 1.5 mm, must be ordered separately

Direction of rotation of the numbering of the contact camera Standard
Encoding N
Connection type of contact Connection set
Type of contacts Female
N. º poles Nineteen
Diameter of contact of the power contacts 1.5 mm
Section min. of braid of contact of power 0.75 mm2
Section max. of braid of contact of power 1 mm2
Rated current per contact power at 25ºC 10 To
Diameter of contact of the signal contacts 1 mm
Section min. of braid of signal contacts 0,08 mm2
Section max. wire braided signal contacts 1 mm2
Rated current per contact signal-to-25ºC 8 To
Environmental conditions
Room temperature -40 °C ... 125 °C
Data according to DIN en 61984:2001
Rated voltage/of Contacts service power 150 V
Rated voltage transient power Contacts 1.5 kV
Category of surge power Contacts II
Degree of dirt power Contacts Three
Rated voltage/of Contacts service signals 150 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-1RS1N8A0000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.