INDUSTRIAL COMPONENT DATA

CAB-MSTB32/2XMC9/18/20,0M/C3/S 2908413 PHOENIX CONTACT Interface cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CAB-MSTB32/2XMC9/18/20,0M/C3/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	CAB-MSTB32/2XMC9/18/20,0M/C3/S
Catalog number	2908413
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-D77823E5C3
Generated	2026-11-18

Product Overview

Interface cable
16-channel VIP cable for use with Honeywell C300 Universal I/O Module, 18 AWG, 20 m length

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2908413
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626685489
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85444290
Country of origin US (United States)
General
Nominal voltage UN < 30 V AC/DC
Max. current carrying capacity per path 2 A
Length of cable 20 m
Single wire, cross section 0.75 mm²
Single wire, cross section [AWG] 18

Conductor construction: Number of litz wires: 16
Single wire, material Cu tin-plated
External diameter 11.8 mm
Shielding yes
Tinned copper-braided shield, approx. 85% covering
Environmental conditions
Ambient temperature (operation) -40 °C ... 90 °C (static)
Ambient temperature (storage/transport) -40 °C ... 90 °C
Flame resistance IEC 60332-1
Connector 1
Connection name Field level
Connection method pluggable
Number of connections 2
Number of positions 18
Pitch 3.81 mm
Connector 2
Connection name Controller level
Connection method pluggable
Number of connections 1
Number of positions 32
Pitch 5.08 mm
Supported controller
Controller Honeywell C300
Standards and Regulations
Flame resistance IEC 60332-1
Classifications
eCl@ss 5.127242200eCl@ss 6.027249200eCl@ss 7.027249205eCl@ss 8.027249205eCl@ss 9.027242220
ETIM 5.0EC000237ETIM 6.0EC000237

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CAB-MSTB32/2XMC9/18/20,0M/C3/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.