INDUSTRIAL COMPONENT DATA

CABLE-50/4FLK14/28,0M/YUC 2901386 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-50/4FLK14/28,0M/YUC



Manufacturer	PHOENIX CONTACT
MPN / Reference	CABLE-50/4FLK14/28,0M/YUC
Catalog number	2901386
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-3DD99EB68F
Generated	2026-11-19

Product Overview

Front adapters
Yokogawa cast iron front adapter with fixed round cable and a 50-pole extrusion-coated plug pin for connection on the 4 x 8 channel field side. Cable length: 28.0 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2901386
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356585729
Weight per Piece (excluding packing) 5,640.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. permissible operating voltage 30 V DC

Max. permissible current 500 mA (per path at 70°C)
Connection data 1
Connection name Control side
Connection method Yokogawa, I/O cards compatible
Torque 0.5 Nm (Screw connection)
Number of connections 1
Number of positions 50
Connection data 2
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 4
Number of positions 14
Pitch 2.54 mm
Cable
Structural data in acc. to UL style 2464/1061
Conductor construction: Number of litz wires: 7
Single wire, cross section 0.14 mm²
External diameter 11 mm
Length of cable 28 m
Outer sheath, material PVC
External sheath, color gray RAL 7035
Shielding yes
Halogen-free cable No
Max. conductor resistance 0.16 ?/m
Cable insulation resistance approx. 153 M?/km
Cable impedance approx. 120 ?
Cable resistance approx. 155 ?/km
Cable capacity approx. 130 pF/m
Insulation Semi-rigid PVC
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card ADV151
ADV551
Controller YOKOGAWA STARDOM
- suitable I/O card NFDV151
NFDV551
Standards and Regulations
Flame resistance IEC 60332-3-22
Resistance to oil DIN VDE 0472 Pa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-50/4FLK14/28,0M/YUC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.