INDUSTRIAL COMPONENT DATA

WT-HT HF 4,5X200 BK 3240787 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HT HF 4,5X200 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-HT HF 4,5X200 BK
Catalog number	3240787
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-CC40274B98
Generated	2026-11-18

Product Overview

Cable tie
Thermoset cable ties up to 125 °C (short-term up to 145 °C) for fast and safe bundling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 3240787
Packing unit 100 pc
Minimum order quantity 100 pc
Catalog page Page 661 (C-3-2017)
GTIN 4046356705059
Weight per Piece (excluding packing) 1.390 g
Custom tariff number 39269097
Country of origin IT (Italy)
Dimensions
Length (b) 200 mm
Width (a) 4.8 mm
Cable diameter 3 mm ... 50 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C

Ambient temperature (assembly) -10 °C ... 60 °C
Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture.To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Short-term temperature 145 °C
General
Color black
Type Internal teeth
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA 6.6
Tensile strength 220 N
Standards and Regulations
Flammability rating according to UL 94 V2
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold val...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HT HF 4,5X200 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.