INDUSTRIAL COMPONENT DATA

WT-E HF 7,8X380 3240726 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-E HF 7,8X380



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-E HF 7,8X380
Catalog number	3240726
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-97F0B0748E
Generated	2026-11-18

Product Overview

Cable tie
Cable holders with clamping button for screwing or riveting, perfect for long-lasting fixation almost in any subsoil

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 3240726
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
Catalog page Page 662 (C-3-2017)
GTIN 4046356704427
Weight per Piece (excluding packing) 6.340 g
Custom tariff number 39269097
Country of origin TW (Taiwan)
Dimensions
Length (b) 380 mm
Width (a) 7.8 mm
Hole diameter 6.5 mm
Cable diameter 4 mm ... 104 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (assembly) -10 °C ... 60 °C
Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture.To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Short-term temperature 110 °C
General
Color transparent
Type Internal teeth
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA 6.6
Tensile strength 540 N
Standards and Regulations
Resistance to UV radiation no
Flammability rating according to UL 94 V2
Environmental Product Compliance
China RoHS Envir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-E HF 7,8X380 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.