INDUSTRIAL COMPONENT DATA

CABLE-FLK14/AXIO/OE/0,14/4,0M 1369906 PHOENIX CONTACT Ready-made round cable. Control: Axioline Realtime I/O..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-FLK14/AXIO/OE/0,14/4,0M



Manufacturer	PHOENIX CONTACT
MPN / Reference	CABLE-FLK14/AXIO/OE/0,14/4,0M
Catalog number	1369906
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-AA3800F4B4
Generated	2026-11-18

Product Overview

Ready-made round cable. Control: Axioline Realtime I/O. Connection 1: Individual conductors (8-poles) (The conductors are labeled and equipped with ferrules). Connection 2: Female IDC/FLK connection (1x 14-pole). Cable length: 4 m
Round cable set; controller: Axioline Realtime I/O; connection 1: Single wires (8-position) (The wires are marked and fitted with ferrules); connection 2: IDC/FLK socket strip (1x 14-position); cable length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type System cable
Environmental and real-life conditionsAmbient conditions
Degree of protection IP00
Degree of protection (Installation location) >= IP54 (Installation location)
Ambient temperature (operation) -40 °C ... 70 °C (fixed installation)
-10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m
Electrical propertiesOperating voltage (AC) <= 30 V AC
Operating voltage (DC) <= 60 V DC

Nominal operating mode 100% operating factor
Current (Per path, 50°C) <= 1 A (Uncoiled, see derating)
Current (Per path, 70°C) <= 0.6 A (Uncoiled, see derating)
Supported controller PHOENIX CONTACT Axioline
Suitable I/O card AXL F DI16...
AXL F DI32...
AXL F DI64...
AXL F DO16...
AXL F DO32...
AXL F DO64...
AXL F DI16/DO16...
AXL F DI16/DO8...
AXL SE DI16...
AXL SE DO16...
Cable/lineCable length 4 m
10X0.14 [PVC]
UL AWM Style 2464/1061
Number of positions 10
Shielded no
Cable type 10X0.14 [PVC]
Conductor type Round cable set
Conductor structure signal line 7x 0.16 mm
AWG signal line 26
Conductor cross section 10x 0.14 mm²
Wire diameter incl. insulation 1 mm ±0.03 mm
External cable diameter 6.1 mm ±0.4 mm
Outer sheath, material Semi-rigid PVC
External sheath, color gray
Conductor material Tin-plated Cu litz wires
Cable resistance <= 145 ?/km (20 °C)
Insulation resistance >= 20 M?*km (20 °C)
Smallest bending radius, fixed installation 52 mm
Smallest bending radius, movable installation 98 mm
Max. ben...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-FLK14/AXIO/OE/0,14/4,0M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.