INDUSTRIAL COMPONENT DATA

# CABLE-FLK40/4FLK14/HF/S7/2,0M 1464628 PHOENIX CONTACT Round cable made without halogens. Connection 1: Femal..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-FLK40/4FLK14/HF/S7/2,0M**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | CABLE-FLK40/4FLK14/HF/S7/2,0M |
| Catalog number | 1464628 |
| Category | PLC connection cable |
| Minimum order | 1 Pcs |
| Document ID | EO-819C481DD8 |
| Generated | 2026-11-19 |

## Product Overview

Round cable made without halogens. Connection 1: Female IDC/FLK connection (1x 40-poles). Connection 2: Female IDC/FLK connection (4x 14-pole). Cable length: 2 m
Cable
Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 40-position); connection 2: IDC/FLK socket strip (4x 14-position); cable length: 2 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Technical dataProduct propertiesProduct type System cable
Environmental and real-life conditionsAmbient conditions
Degree of protection IP00
Degree of protection (Installation location) >= IP54 (Installation location)
Ambient temperature (operation) -40 °C ... 50 °C (fixed installation)
-10 °C ... 50 °C (flexible installation)
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m
Electrical propertiesOperating voltage (AC) <= 30 V AC

Operating voltage (DC) <= 60 V DC
Nominal operating mode 100% operating factor
Current (Per path, 50°C) <= 1 A (Uncoiled, see derating)
Current (Per path, 70°C) <= 0.6 A (Uncoiled, see derating)
Supported controller SIEMENS S7-1500
Suitable I/O card 6ES7521-1BP00-0AA0 (Sinking mode)
6ES7522-1BP00-0AA0
6ES7522-1BP50-0AA0
6ES7523-1BP50-0AA0 (DI32 (Sinking mode)/DQ32)
Cable/lineCable length 2 m
Number of positions 14
Shielded no
Conductor type Assembled, halogen-free round cable
Conductor structure signal line 7x 0.16 mm
AWG signal line 26
Conductor cross section 14x 0.14 mm²
Wire diameter incl. insulation 1 mm ±0.03 mm
External cable diameter 5.8 mm ±0.4 mm
Outer sheath, material halogen-free (type 2)
External sheath, color gray
Conductor material Tin-plated Cu litz wires
Cable resistance <= 145 ?/km (20 °C)
Insulation resistance >= 20 M?*km (20 °C)
Smallest bending radius, fixed installation 50 mm
Smallest bending radius, movable installation 93 mm
Max. bending cycles 5000 (at a radius of >= 15x outside diameter)
Halogen-free yes
Fla...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-FLK40/4FLK14/HF/S7/2,0M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.