INDUSTRIAL COMPONENT DATA

G-INS-NPT1/2-S68L-NNES-S 1411183 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-NPT1/2-S68L-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-NPT1/2-S68L-NNES-S
Catalog number	1411183
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-5A17EC7643
Generated	2026-11-19

Product Overview

Cable gland
Cable gland, screwed connection material: Brass, nickel-plated, cable outer diameter 10 mm ... 14 mm, shielding: no, connection thread: 1/2" NPT, color: silver, with O-ring
Cable gland, material gland: brass, nickel-plated, application: standard, cable outer diameter 10 mm ... 14 mm, shielding: no, connection thread: 1/2 inch NPT, color: silver-colored, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1411183
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 687 (C-4-2015)
GTIN 4046356923156
Weight per Piece (excluding packing) 36.110 g
Custom tariff number 74199990
Country of origin TR (Turkey)
Dimensions
Length 39 mm

Wrench size, union nut 22 mm
Wrench size, support 22 mm
Hexagon angular dimension 29.7 mm
Length of the connecting thread 13 mm
External cable diameter 10 mm ... 14 mm
10 mm ... 12 mm (for UL 514 B)
Ambient conditions
Degree of protection (IP) IP68
Degree of protection (NEMA) 4X
Ambient temperature (operation) -40 °C ... 100 °C (static)
General
No. of conductors 1
Cable gland material Nickel-plated brass
Material, insert Polyamide 6
Cable seal material Neoprene
Sealing material Perbunan (O-ring)
Shielded no
Thread type connection side 1/2 inch NPT
Thread type on connection side 1/2 inch NPT
Torque 10 Nm ... 13 Nm (Union nut: EN 62444)
15 Nm ... 20 Nm (Support: EN 62444)
6 Nm (for UL514 B: union nut)
Color silver
Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
Manufacturer BIMED
Manufacturer Designation BNBC-02
Standards and Regulations
Halogen-free no
Connection in acc. with standard UL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127081000eCl@ss 6.027149100eCl@ss 7.027149109eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-NPT1/2-S68L-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.