INDUSTRIAL COMPONENT DATA

G-INS-PG42-L68N-NNES-S 1411179 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-PG42-L68N-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-PG42-L68N-NNES-S
Catalog number	1411179
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-23F08B95B1
Generated	2026-11-19

Product Overview

Cable gland
Cable gland, screwed connection material: Brass, nickel-plated, cable outer diameter 30 mm ... 38 mm, shielding: no, connection thread: Pg42, colour: silver, with O-ring
Cable gland, screw connection material: Brass, nickel plated, application: Standard, outer diameter of the cable 30 mm ... 38 mm, shielding: no, connection thread: Pg42, colour: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1411179
Packing unit 1 pc
Catalog page Page 697 (C-2-2017)
GTIN 4046356923125
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 74199990
Country of origin TR (Turkey)
Dimensions
Length 60 mm
Wrench size, union nut 58 mm

Wrench size, support 58 mm
Hexagon angular dimension 64 mm
Length of the connecting thread 12 mm
Feed-through hole diameter 54.1 mm ... 54.5 mm
External cable diameter 30 mm ... 38 mm
30 mm ... 38 mm (for UL 514 B)
Ambient conditions
Degree of protection (IP) IP68 (5 bar, 30 min.)
Ambient temperature (operation) -40 °C ... 100 °C (static)
General
No. of conductors 1
Cable gland material Nickel-plated brass
Material, insert Polyamide 6
Cable seal material Neoprene
Sealing material Perbunan (O-ring)
Shielded no
Thread type connection side Pg42
Thread type on connection side Pg42
Torque 27 Nm (Union nut: EN 62444)
27 Nm (Support: EN 62444)
30 Nm (for UL514 B: union nut)
Color silver
Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
Manufacturer BIMED
Manufacturer Designation BSBC-09
Standards and Regulations
Halogen-free no
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127081000eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432
ETIM 4.0EC000441ETIM 5.0EC000441ETIM 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-PG42-L68N-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.