

INDUSTRIAL COMPONENT DATA

G-INS-M32-M68N-NNES-S 1411166 PHOENIX CONTACT Cable gland, Cable gland material: Brass, nickel-plated, Exter..

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-M32-M68N-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-M32-M68N-NNES-S
Catalog number	1411166
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-53785E0706
Generated	2026-09-22

Product Overview

Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 15 mm ... 21 mm, Shielding: No, Connecting thread: M32, Color: silver

Cable gland, screwed connection material: Brass, nickel-plated, outer diameter of the cable 15 mm ... 21 mm, shielding: no, connection thread: M32 x 1.5, colour: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions

Length 43 mm

Wrench size, union nut 34 mm

Wrench size, support 34 mm

Hexagon angular dimension GRP 37 mm

Length of the connecting thread 8 mm

External cable diameter 15 mm ... 21 mm

Ambient conditions

Degree of protection IP69K

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

Cable gland material Brass, nickel-plated

Seal material Neoprene
Cable seal material Neoprene
O-ring material NBR
Shielded No
Thread type on connection side M32
Torque 8 Nm (Union nut)
Color silver

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-M32-M68N-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.